



Multi Surface Paint

Ref: JR379

1. Introduction

A self-priming acrylic based paint designed for application to a multitude of different surfaces. Specialist anti-corrosive additives provide exceptional resistance to weathering for improved exterior durability.

2. Where to use

Can be applied to most rigid surfaces including metal, wood, plastics and ceramics.

3. Where not to use*

- Previously painted surfaces without prior compatibility assessment.
- UPVC
- PP composites without prior application of an adhesion aid.
- Flexible, soft or waxy plastics such as HDPE and polystyrene.

*If unsure of suitability it is recommended to test compatibility before first use.

4 Benefits

- Excellent covering power
- Self-Priming
- For use on multiple different surfaces
- 500+ hours salt spray resistance to ASTM B-117
- Smooth matt finish
- Quick drying
- Non-yellowing

5. Physical properties

Appearance	Coloured viscous liquid
pH [10% aqueous solution]	N/A, solvent based
Specific Gravity	0.95 – 1.2, colour dependant (aerosol concentrate)
Flammability, as Supplied	Extremely Flammable
Application Temperature	For use on cool surfaces, at ambient temperatures.
Composition	A solvent based solution of an acrylic resin containing a range of pigments, extenders, plasticizers and thixotropes dispersed in a butane/propane/isobutane based propellant.

6. Application Details

Prepare the area to be treated, ensuring freedom from dust, grime, greases, oils etc, with a solvent wipe using white spirit, thinners or a proprietary panel wipe and allow to dry.

If necessary, the surface may be flattened by abrading the surface lightly, using 1200 grade wet and dry abrasive paper, and solvent treated as described above to remove any dust.

Shake the can thoroughly for at least two minutes. Repeat shaking at regular intervals during use.

This information is provided in good faith based upon data and sources believed to be reliable and correct. Conditions of use, outside the control of the Company, dictate that no responsibility can be assumed for the ultimate performance of this product.

Apply sparingly from a distance of 20 - 25cm. Apply typically 2 to 3 coats or as necessary to achieve total and even coverage, leaving between 10 and 20 minutes between each application.

Allow to dry for 24 hours to develop maximum paint hardness.

On completion of use, invert can and depress actuator for a few seconds to prevent nozzle blockage.

This information is provided in good faith based upon data and sources believed to be reliable and correct. Conditions of use, outside the control of the Company, dictate that no responsibility can be assumed for the ultimate performance of this product.